

ZERUST Film for Ferrous Metals

ZERUST Film creates rust inhibiting environment inside bag to protect contents from corrosion. Please read and follow these directions thoroughly.

How To Use

- Degrease item or component before placing in bag.
(Make sure item does not have oil coating.)
- After item is placed in bag, seal well, such as with adhesive tape to prevent exposure to outside air. (Anti-rust properties will last three years from date of purchase. If not sealed, this period will be significantly reduced.)

⚠ Storage Notes

- Use as soon as possible after opening; Anti-corrosion film is volatile.
- Re-seal package immediately to prevent exposure to air. If anti-rust chemicals are allowed to evaporate, the protection may be significantly reduced.
- Store at temperature below 30°C (85°F), Less than 50%RH, and out of direct sunlight.
(Storage at higher temperatures will increase vaporization and significantly reduce anti-rust protection period.)
- During storage, the ZERUST Film color may change dependent on storage time and temperature. Color change does not affect the anti-corrosive properties.

⚠ Precautions

- For ferrous items. (Iron and Steel.)
- Clean and degrease to remove all dirt, moisture, and contamination from item to be stored.
- Handle item with gloves before placing into bag to prevent contamination with hand sweat and oils, which may cause rust.
- After placing item into bag, please seal with adhesive tape to prevent outside air from entering.
- Remove all packing and cushioning material from item before placing inside ZERUST bag. If item is in direct contact with cardboard, paper, Styrofoam, etc, rust may form at point of contact.
- Use only as directed.

SC Niigata seiki Co., Ltd.

6-15-22, Tsukanome, Sanjo, Niigata, Japan, 955-0055

Tel. : +81-256-31-5670 Fax. : +81-256-39-7730

MAIL: intl.sales@niigataseiki.co.jp

URL <http://www.niigataseiki.co.jp>

I277-K1 1702

Record Date of Purchase:

Year _____ Month _____ Day _____

• Expiration: 3 Years after date of purchase.

(Rec. Storage: 30°C (85°F), ≤ 50%RH, dark)

• Keep unused product in sealed package.