

# Niigataseiki High Accuracy Digital Level Series

High resolution -  
**0.001mm/m**

**Built-in wireless**

**With battery status  
check function!**

Unlike bubble level, DL-S4We enables easier and quicker measurement up to 0.001 mm/m digit with no risk of mis-reading.

# LEVELNIC DL-S4We



## High Accuracy Digital Level --- LEVELNIC

### WIRELESS DATA TRANSMISSION

Equivalent to Bluetooth SPP/Communication range 30~40m

### SWITCHABLE BETWEEN WIRED AND WIRELESS

Save electricity, dedicate long time use

### USB RECEIVING UNIT

The driver is supported  
By the automatic recognition system

### BATTERY STATUS CHECK FUNCTION

Prevents unexpected battery depletion  
during measurement

#### ACCESSORIES

- USB receiving unit
- Dedicated data recording software
- AC adapter
- Two 1.5v AA batteries
- Shock resistant aluminum case
- Instruction manual

### SPECIFICATIONS

Measuring range <sup>※1</sup>	±5.00mm/m ±0.286°
Minimum reading	0.001mm/m 0.0001° (Within ±1.999mm/m) 0.01mm/m 0.001° (More than ±2mm)
Operating temperature range	0~40°C
Reading accuracy <sup>※2</sup> (20±3°C)	±0.85%rdg (Within ±1.999mm/m) ±1.0%rdg (More than ±2mm/m)
Reading accuracy <sup>※2</sup> (20±20°C)	±2.6%rdg (Within ±1.999mm/m) ±2.7%rdg (More than ±2mm/m)
Repeat accuracy	Within ±0.005mm/m, ±0.0003°
Output signal	Conform to RS-232C wired Built-in wireless system (Equiv. Bluetooth SPP/ Communication range 30~40m)
Power source	Two 1.5V AA batteries AC adapter (DC 3V Output)
Battery life under <sup>※3</sup> continuous operation	Manganese battery : Approx. 20 hours (Attempting wireless operation 15 hours) Alkaline battery : Approx. 50 hours (Attempting wireless operation 40 hours)
Outer dimensions	158(L)×61(W)×107(H) mm
Base dimensions	150(L)×55(W) mm
Weight	Approx. 2.0kg

※ 1 : When DEG (°) measurement mode, display only shows numbers after the decimal point.  
For 0.001mm/m (0.0001°) display mode, maximum reading which can be displayed is less than ±1.999mm/m (±0.1145°).

※ 2 : %rdg indicates percentage of displayed value.

※ 3 : May vary depending upon measurement conditions.

※ The appearance and specifications are subject to change without notice for product improvement.

※ There may be a slight difference in color between the printed material and the actual product.

**SC Niigata Seiki Co., Ltd.**

5-3-14, Tsukanome, Sanjo, Niigata, Japan, 955-0055  
Tel. : +81-256-33-5522 Fax. : +81-256-33-5518  
MAIL intl.sales@niigataseiki.co.jp  
URL <https://www.niigataseiki.net/en/>

No2603

■ Distributor