




MICROMETER HEAD



224p



224p




224p



224p




224p




225p



225p



225p



226p




226p




227p



227p



228p



228p



228p

Micrometer head Size Lineup

※Background grid: approx. 10mm

■ Measuring Range
0~5.0mm



0000-050 P225



0010-050 P225

■ Measuring Range
0~6.5mm



MH-65KD P224



1001-050 P225



1011-050 P225



1001-350 P225



1011-350M P225

■ Measuring Range
0~13mm



MH-130KD P224



1002-050 P226



1012-050 P226



1002-350 P226



1012-350 P226



1702-050 P226



1712-050 P226



1702-350 P226



1712-350 P226

■ Measuring Range
0~15mm



1002-250 P227



1012-250 P227



1009-350 P227



1019-350 P227



1709-050 P227



1719-050 P227



1709-350 P227



1719-350 P227

■ Measuring Range 0~25mm



MH-250KD P224



1603-000 P228




T1003-000D P228



1003-310 P228



1003-010 P228



1703-010 P228



1803-300 P228



1703-310 P228



1813-300 P228




Spindle 1mm pitch 1004-000 P228




1813-310 P228




1003-000 P228



Spindle 1mm pitch 1004-030 P228



QEM403-25F P224



QEM413-25S P224

MICRO
METER
HEAD

DIGITAL MICROMETER HEAD



Digital type. To be mounted on measuring instruments or use as feeding device or stopper, not for single use.

● Measuring range: 0 ~ 25mm



QEM403-25F




QEM413-25S




● DIMENSIONS

Units: mm



QEM403-25F



QEM413-25S

USE

- Mount on precision equipment or machinery to measure, position and feed

MATERIAL

- Thimble: Carbon steel for machine structural use
- Spindle: High carbon chromium steel

FEATURES

- Quick digital display of the measured value
- Standard and general purpose with measuring range 0~25mm
- Carbide tipped measuring face for wear resistance
- Auto display off function (after approx. 20 min.)
- With ratchet stop

POWER

- One CR2032 (lithium) battery included for testing

※ Quantization Error (± 1digit) not included

Order No.	Model No.	Stem	Spindle Dimension (mm)	Stem Dimension (mm)	Spindle Face	Resolution (mm)	Maximum Permissible Error※ (μm)	Length (mm)	Thimble Diameter (mm)	Weight
NEW! 152341	QEM403-25F	Straight	φ6.5×28.5	φ12×17.5	Flat	0.001	3	162	18	220g
NEW! 152342	QEM413-25S				Spherical (SR5)					



MICROMETER HEAD KAIDAN



New stepped millimeter graduations prevents misreading.

To be mounted on measuring instruments or use as feeding device or stopper, not for single use.

- Measuring Range: 0 ~ 6.5mm
- Measuring Range: 0 ~ 13mm
- Measuring Range: 0 ~ 25mm



MH-65KD



MH-130KD



MH-250KD

USE

- Mount on precision equipment or machinery to measure position and feed

MATERIAL



- Thimble: Alloy tool steel
- Spindle: High carbon chromium steel

FEATURES


- Easy reading Kaidan series
- Carbide tipped measuring face (MH-250KD)

● DIMENSIONS


Units: mm



MH-65KD



MH-130KD




MH-250KD

Order No.	Model No.	Stem	Spindle Dimension (mm)	Stem Dimension (mm)	Spindle Face	Resolution (mm)	Maximum Permissible Error (μm)	Length (mm)	Thimble Diameter (mm)	Weight
151147	MH-65KD	Straight	φ3.5×9	φ6×6	Flat	0.01	5	37	9.5	10g
151148	MH-130KD		φ5×17	φ9.5×9.5			4	58.5	13	35g
151149	MH-250KD		φ6.5×27	φ10×15			3	99.5	18	90g


0

MICROMETER HEAD

To be mounted on measuring instruments or use as feeding device or stopper, not for single use




● Measuring Range: 0 ~ 5.0mm



● DIMENSIONS

Units: mm



USE

- Mount on precision equipment or machinery to measure position and feed

MATERIAL

- Thimble: Alloy tool steel
- Spindle: High carbon chromium steel

FEATURES


- Measuring range: 0~5mm, small and lightweight
- With spindle fixing screw

Order No.	Model No.	Stem	Spindle Dimension (mm)	Stem Dimension (mm)	Spindle Face	Resolution (mm)	Maximum Permissible Error (μm)	Length (mm)	Thimble Diameter (mm)	Weight
151145	0000-050	Straight	φ2×6.5	φ3.5×5	Flat	0.02	5	32	6	4g
151146	0010-050				Spherical (SR1.5)					

MICROMETER HEAD

0

To be mounted on measuring instruments or use as feeding device or stopper, not for single use




● Measuring Range: 0 ~ 6.5mm



1001-050

● DIMENSIONS

Units: mm



USE

- Mount on precision equipment or machinery to measure position and feed

MATERIAL

- Thimble: Alloy tool steel
- Spindle: High carbon chromium steel

FEATURES


- Measuring range: 0~6.5mm, small and lightweight

Order No.	Model No.	Stem	Spindle Dimension (mm)	Stem Dimension (mm)	Nut (mm)	Spindle Face	Resolution (mm)	Maximum Permissible Error (μm)	Length (mm)	Thimble Diameter (mm)	Weight
151134	1001-050	Straight	φ3.5×9	φ6×6	—	Flat	0.01	5	37.5	9.5	10g
151135	1011-050					Spherical (SR3)					
151136	1001-350	Threaded	φ3.5×7.5	φ6×7.5	φ8×3	Flat					
151150	1011-350M					Spherical (SR3)					

MICROMETER HEAD

To be mounted on measuring instruments or use as feeding device or stopper, not for single use

● Measuring Range: 0 ~ 13mm





1002-050



1702-350

Units: mm

● DIMENSIONS



USE

- Mount on precision equipment or machinery to measure position and feed

MATERIAL

- Thimble: Alloy tool steel
- Spindle: High Carbon chromium steel

FEATURES


- Measuring range: 0~13mm, small, general-purpose series

Order No.	Model No.	Stem/ Spindle Clamp	Spindle Dimension (mm)	Stem Dimension (mm)	Nut (mm)	Spindle Face	Resolution (mm)	Maximum Permissible Error (μm)	Length (mm)	Thimble Diameter (mm)	Weight
151110	1002-050	Straight	ϕ5×17.5	ϕ9.5×9.5	—	Flat	0.01	4	59.5	13.5	35g
151111	1012-050					Spherical (SR4)					
151112	1002-350	Threaded			ϕ14×4	Flat					
151113	1012-350					Spherical (SR4)					
151114	1702-050	Straight / with Clamp	ϕ5×17		—	Flat			67	13	45g
151115	1712-050					Spherical (SR4)					
151116	1702-350	Threaded / with Clamp			ϕ14×4	Flat					
151117	1712-350					Spherical (SR4)					

MICROMETER HEAD

To be mounted on measuring instruments or use as feeding device or stopper, not for single use

● Measuring range: 0 ~ 15mm




1709-050



1719-350

● DIMENSIONS

Units: mm



USE

- Mount on precision equipment or machinery to measure position and feed

MATERIAL

- Thimble: Alloy tool steel
- Spindle: High carbon chromium steel

FEATURES


- Measuring range: 0~15mm small, general-purpose series
- Carbide tipped measuring faces (1709-050, 1719-050, 1709-350, 1719-350)

Order No.	Model No.	Stem/ Spindle Clamp	Spindle Dimension (mm)	Stem Dimension (mm)	Nut (mm)	Spindle Face	Resolution (mm)	Maximum Permissible Error (μm)	Length (mm)	Thimble Diameter (mm)	Weight
151118	1002-250	Straight	φ5×17		—	Flat	0.01	4	61	13.5	40g
151119	1012-250					Spherical (SR4)					
151120	1009-350	Threaded		φ9.5×9.5	φ14×4	Flat			75.5	15	65g
151121	1019-350					Spherical (SR4)					
151122	1709-050	Straight / with Clamp	φ6.5×17		—	Flat					
151123	1719-050					Spherical (SR4)					
151124	1709-350	Threaded / with Clamp			φ14×4	Flat					
151125	1719-350					Spherical (SR4)					

MICROMETER HEAD

0

To be mounted on measuring instruments or use as feeding device or stopper, not for single use



● Measuring Range: 0 ~ 25mm



T1003-000D




1813-310




1004-000

● DIMENSIONS


Units: mm




T1003-000D




1813-300




1703-010




1003-010




1813-310




1703-310



1803-300




1003-000




1004-000

Spindle 1mm pitch



1603-000



1004-030

Spindle 1mm pitch

USE


- Mount on precision equipment or machinery to measure position and feed

MATERIAL

- Thimble: Alloy tool steel
- Spindle: High carbon chromium steel

FEATURES

- Measuring range: 0~25mm small, general-purpose series
- Carbide tipped measuring faces (exclude 1813-300)
- Spindle 1mm pitch (1004-000, 1004-030)



1003-310

Order No.	Model No.	Rachet	Stem / Spindle Clamp	Spindle Dimension (mm)	Stem Dimension (mm)	Nut (mm)	Spindle Face	Resolution (mm)	Maximum Permissible Error (μm)	Length (mm)	Thimble Diameter (mm)	Weight
151138	T1003-000D	None	Straight	φ6.5×27	φ10×15	—	Flat	0.01	3	98.5	18	90g
151126	1003-010	Yes		φ6.5×28	φ11×16.5					109		
151139	1803-300	None	Threaded	φ6.5×27	φ10×15	φ14×4	Spherical (SR4)			98.5		
151141	1813-300									108		
151140	1813-310	Yes	Straight	φ6.5×28.5	φ12×17.5	—	Flat			113	95g	
151127	1003-000									118	100g	
151128	1603-000		118	110g								
151129	1003-310		Threaded	φ6.5×27	φ10×15	φ14×4	108			95g		
151130	1703-010		Straight / with Clamp			—	121			115g		
151131	1703-310		Threaded / with Clamp			φ14×4	121		120g			
151133	1004-000		Straight	φ8×28.5	φ12×17.5	—			4	115	29	230g
151132	1004-030	113								30	200g	